



Multifunctional premium-class compact 2-way system. The coaxial configuration in combination with a carefully designed large-area horn ensures absolutely constant response even off the main axis. High-power Neodym drivers and long-excursion coils provide high efficiency and reduced distortion. Nine M10 threaded mounting points are available to mount MultiRigg hardware and other accessories for installation or mobile applications.

#### **PRODUCT SPECIFICATIONS**


Speaker Components	10" Nd (3" VC) / 1" Nd (1,7" VC)
Description	Multifunctional Coaxial Sound System
Power AES / Peak	350 W / 1000 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	97 dB / 127 dB
Usable Range	60 Hz - 19 kHz (-6 dB)
Tuning Frequency Excursion minimum	70 Hz
X - Overpoint acoustical	1,2 kHz
Coverage horizontal / vertical	80° x 60° - rotatable
Connectors	2 x Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru
Handles	2 x
Rigging / Fittings	9 x M10 To be used with MultiRigg 35 mm pole mount
Weight	12,5 kg
Size height x width x depth	45,0 x 31,0 x 29,0 cm
Order No.	01093
















4 x M10 Twinpoints for MultiRigg™












**Controller Setups**:




https://www.seeburg.com/en/downloads

# **MEASUREMENTS**






# Sensitivity 1 W @ 1 m + Impedance



# 2D Directivity Plot - vertical



# **Frequency Response with Presets**



# MultiRigg™

swiveling fastening solution for horizontal and vertical alignment, for flown / ground stacked / mounted applications, incl. accessories (2 x knurled screws M10 x 20 mm, 1 x handle screw M8 x 55 mm), max. load 50 kg

Order No. 01360



#### MultiRigg™ light

version for fixed installations, for horizontal and vertical alignment, tiltable vertical angle, incl. accessories (2 x M10 x 20 socket head screws), max. load 50 kg

Order No. 01362



# MultiTilt™

Tilt adapter with adjustable tilt from  $0^{\circ}$  to 37,5° (2,5° steps), integr. pole mount adapter with clamping device, 2 x knurled screws (M10 x 20 mm), max. load 50 kg

Order No. 01370



### **Knurled Screw**

M10 x 20 mm



Order No. 73750/w (RAL 9010)

Order No. **73750** 



#### **Knurled Head Nut**

reduction screw for fastening M10 Pole Mount Adapter (08126)

Order No. 73755

# **Pole Mount Adapter**



35 mm ø -> M10 x 16 mm, M8 x 20 star knob screw Order No. 08126

35 mm ø -> M10 x 16 mm

Order No. 08126/II



#### **Steel Safety**

6 mm x 600 mm, black, max. load 22 kg (BGI 810-3), quick connector undetachably

Order No. 01376/6



#### TV Spigot

10 mm internal thread, 28 mm Ø

Order No. 08128



#### **Ring Screw**

M10-DIN 580

Order No. **73700** (zinced)

Order No. 73700/sw (black zinced)



#### **Quick Trigger Clamp**

max. load 100 kg

Order No. 01223/100 kg





M10, max. load 20 kg

Order No. 01223/20 kg



MultiRigg™light



MultiRigg™





#### **ACCESSORIES X 4**

#### Adapter



for X 4, X 6, X 8 for mounting with Wall Mount (03034), incl. 2 x M10 x 20 socket head screws

Order No. **01198/w** (RAL 9010) Order No. **01198** 

#### **Wall Mount**



2 x M6 fixing holes (d=73 mm), 1 x M10 fixing hole (center), max. load 25 kg

Order No. **03034/w** (RAL 9010) Order No. **03034** 

## **Wall Mount**



bar: 269 mm, max. load 40 kg, incl. (M10 x 70 mm socket head screw, M10 hex lock nut and flat washer)

Order No. **08130/F/269/w** (RAL 9010) Order No. **08130/F/269** 

#### **Wall Mount**



with tilt unit, max. load 40 kg Order No. **08130** 

# Cover



for X 4, padded

Order No. 01225/X4

#### **Rain Cover**



for X 4, with zipper

Order No. 01225/X4/outdoor

#### **Flight Case**



for 2 pcs. X 4 and 2 pcs. MultiRigg, partition walls, heavy duty, 9 mm birch multiplex, PVC coated black, 6 x recessed sprung handles, 1 x butterfly catch, 4 x 100 mm blue wheels (2 pcs. with brake), interior lined with felt
Size (H x W x D): 63 x 61,5 x 59 cm

Order No. 16560











Rain Cover

